First lightship-based wind lidar measurement in the North Sea



OffshoreWind2018 – Topic: 6. Beurteilung von Ressourcen

Bremerhaven, 14. November 2018

Beatriz Cañadillas, Friedrich Wilts, Richard Foreman, Tom Neumann, UL International GmbH

Empowering Trust[™]

UL and the UL logo are trademarks of UL LLC © 2018.

Outline

- 1. Project motivation
- 2. Location
- 3. Measurements overview
- 4. Overall system availability/reliability
- 5. Ship-movements influences on wind lidar measurements
- 6. 10-min comparisons with Helgoland wind lidar
- 7. Comparison with airborne measurements above the lightship
- 8. Summary
- 9. Next-steps



Photo: Astrid Lampert, TU Braunschweig







1. Project Motivation



Main motivation: As a part of the ongoing project **WIPAFF*** (Wind Park Far Field), this measurement campaign aims to collect long-term wind profiles under both, free and wind farm far-wake conditions.

• Evaluation of vessel** movement effects on the wind lidar measurements, system stability, and performance in different weather conditions.

<u>Side topic</u>: To assess the extent to which existing offshore infrastructure can be used for continuous monitoring of the marine boundary layer as supplement to bespoke monitoring infrastructure such as the FINO platforms.

*The WIPAFF project is funded by the German Federal Ministry of Economic Affairs and Energy (grant number: FKZ0325783) on the basis of a decision by the German Bundestag.



**The lightship is operated by the Wasser und Schiffahrtsamt (WSA) Wilhelmshaven and is also used by the Federal Maritime Agency (BSH) as a part of the Marnet monitoring network.





WIPAFF



WIPAFF

3. Measurements overview (II)

1	Sensor type	Parameters	Time Resolution	Height above mean sea level [m]	Photos
	Wind lidar (WindCube v2, WLS7-576)	Wind Speed & Direction, internal status parameters (e.g. availability, CNR,)	~ 1Hz /10- min	71.5, 81.5, 91.5, 102.5, 119.5, 139.5, 159.5, 179.5, 199.5, 249.5, 279.5, 295.5	WINDCUBE
	IMU Sensor (3DM- GX3-35 Microstrain)	Euler angles (Pitch, Roll, Yaw) & angular rates (Ω _x , Ω _y , Ω _z)	10Hz	5.5	3DM-GX3 -35 Attitude Heading Reference System with GPS - R5222/USB e5223 - 4220.01091 x
	Thales 3011 Dual-GPS	Ship position & Heading	1Hz	6	
	HS-50 Gill-Sonic anemometer	u, v, w, T _s	10Hz	6	





3. Measurements overview (III)

Sensor type	Parameters	Time Resolution	Height above mean sea level [m]	Photos
PTH sensor	Air temperature, humidity, pressure	~ 1Hz /10- min	6	
Thies Anemometer & Wind vane	Wind Speed & Direction	1min	15	
PT100, 1/3 DIN B	Air temperature		8	
Vaisala HMP45D	Air humidity		8	
Vaisala PTB220	Air pressure		0	
PT100, 1/3 DIN B	SST		-1.5	
Wave-rider Buoy (Station Helgoland North)	Met-Ocean parameters (e.g. wave spectra, significant wave height, peak wave period, current speed and direction, SST)	30min	0	(Photo: BSH)



3. Measurements overview (IV)



Data communication

- Mobile radio modem (3G cell network connection)
- BSH Iridium satellite phone: Daily Status Signals (Back-up)

Data logging system

• Central Industrial PC with external hard disk drive (SSD)

Power Supply

- Diesel Generators
- UPS (Batteries): 2 hours time (Back-up)

Maintenance

- Daily monitoring via TeamViewer
- Approx. monthly maintenance will be conducted by BSH Team (e.g. fill-up water container, exchange SSD, visual inspection,...)

Time-synchronization

All datasets are based on GPS time



4. Overall system availability/reliability

Period analyzed: **27.08.17 to 26.08.18** (campaign ongoing) Excluded CNR values <-22dB and NaN values



Data coverage



Number of system failures: 0

Number of maintenances (lightship): 4

- Cleaning lidar window
- Refilling water tank

Number of Unscheduled Outages: 2

- 23-28 February 2018 Failure power supply
- 28.03.18-04.04.18 Failure power supply
- 05.04.18-07.06.18 in port for maintenance

5. Ship-movements: influences on wind lidar measurements

Rotation motions:

- Roll (ϕ): transverse (side-to-side) axis \rightarrow forward
- Pitch (θ): longitudinal (front/back) axis \rightarrow starboard
- Yaw (ψ): about the vertical axis \rightarrow downward

Linear motions:

- Sway: lateral (side-to-side) motion
- Surge: longitudinal (front-back) motion
- Heave: vertical (up/down) motion



Definition of Vessel Motions in Six Degrees of Freedom (Photo: BSH)





5. Vessel-movements: influences on wind lidar measurements





5. Example: Two different vessel-movement conditions



high ship motion

low ship motion



Definition of "high sea state": angles exceeding \pm 10°



5. Example: Two different vessel-movement conditions → Effects



6. 10-min comparisons with Helgoland wind lidar (I)

Spatial-Variation*				
Location	Scaling factors			
LShip/ Helgoland	1.008			
LShip/AV Sub-station	1.003			

* Based on 4-Years (2007-2010) In-House Mesoscale simulations at 90m







Theoretical time-delay for a stationary flow

Source: Google maps





Wind sector selected: 150°-220°







6. 10-min comparisons with Helgoland wind lidar (II)

Reference data: WindLidar Helgoland (WindCube WLS8-8)

Experimental data: WindLidar Lightship (WindCube v2)

Measurement Period: 2017/08/27 00:10 - 2018/03/22 23:50





Flight track on 14 October 2017 (aircraft Dornier 128-6, operated by the TU Braunschweig)

7. Comparison with airborne measurements (II)





14.10.2017

- Wind direction = 230°
- Δ roll= $\pm 1.5^{\circ}$, Δ pitch= $\pm 4^{\circ}$



8. Summary



- Reliable long-term (>1year) wind lidar measurements can be performed on a lightship.
- Very good availability
- Movement correction important for pitch/roll angles > 8-10°
- Useful dataset for wind data/model validation

9. Next steps

- Analysis of wind lidar turbulence
- Development of a method to detect long wakes
- New lightship (UFS03) wind lidar measurements by the end November 2018





Acknowledgements

• We would like to thank to our colleagues Hauke Decker and Christian Krüger for the system installation, the teams of K. Herklotz from the "Federal Maritime and Hydrographic Agency, BSH", H. Kleta from "German Weather Service, DWD" and M. Bredow from "Wasserstraßen- und Schifffahrtsamt, Wilhelmshaven" for their technical/logistic support during the first stage of the measurement set up on the lightship.



Thank you for your attention!

Beatriz Cañadillas beatriz.canadillas@ul.com | T:: +49 441 77937 129



Empowering Trust[™]

UL and the UL logo are trademarks of UL LLC © 2018.